



DISPLAX Skin Fit

TOUCH PERFORMANCE AND VERSATILITY

- **High speed**
- **Versatile and adaptable product**
- **Wide range of glass thickness**
- **Features XTR-Shield™ Plus, the most advanced generation of DISPLAX's proprietary noise filtering technology.**

Benefits:

Superb touch experience
 Wide variety of applications and use
 Versatility and ease of integration
 Highly customizable

Key features:

Flexible projected capacitive sensor
 40 simultaneous touches
 Sizes from 20" to 105"
 Works with main Operative Systems
 Aspect ratios 16:9, 4:3 and custom formats
 5 milliseconds response time
 Works with glass thickness up to 15 mm
 HID (Human Interface Device) – no drivers required

Typical applications:

Indoor & outdoor kiosks	Indoor kiosks
Custom structures	Wayfinding
Multitouch tables	Shopping window applications

DISPLAX™ Skin Fit

SPECIFICATIONS

GENERAL

Detection method	Projected Capacitive Technology
Input method	Finger and gloved finger
Number of simultaneous touches	40
Sensor thickness	100 micron transparent polymer
Noise Shielding	DISPLAX XTR-Shield™ Plus, a proprietary noise filtering technology
Sizes	20" to 105"
Aspect ratio	16:9, 4:3, custom formats
Controller	Printed circuit board with mini USB connector
Adhesive	Permanent, removable
Substrate	Float Glass, Gorilla Glass
Interface	HID
OS with multitouch	Windows 10, 8, 7*, Ubuntu 12.04, Linux**, Android**, Chrome OS ***
OS with single touch	Mac OS X Yosemite (multitouch support through TUIO bridge)
OS with mouse emulation	Spinetix Media Player HMP 200, Samsung SSP D Series
Data connectivity	USB 2.0
Touch accuracy	0,53% of sensor diagonal
Sensor weight	260 g
Controller weight	42 g
USB cable length	2 m

PERFORMANCE

Substrate thickness	Up to 15 mm
Touch response	5 milliseconds
Finger separation	2,64% of sensor diagonal
Calibration	Available using control panel: no drift

POWER CONSUMPTION

Average power consumption (P)	USB powered @ 5 V Operation consumption: 250 mA
-------------------------------	--

RELIABILITY

Operating temperature range	-20 °C to 70 °C
Storage temperature range	-40 °C to 135 °C
Operating humidity range	0% to 96%
Storage humidity range	0% to 100%, except controller
Touch Sensor life time expectancy	Unlimited
Touch Controller life time expectancy	1 million hours
Warranty	2 years

DISPLAX™ Skin Fit is designed, manufactured and assembled in EU

*Home Premium SP1; Professional SP1; Ultimate x64 SP1

** Depending on kernel and multitouch support. Contact us for further discussion

*** 39.0.2171.85(64-bit)

DISPLAX
Multitouch
Technologies

Address (Head-Office):
Rua Soldado Manuel Pinheiro
Magalhães, 68
4710 - 167 Braga
Portugal

Web
www.displax.com

E-mail
touch@displax.com

Phone
+351 253 141 500

